

Banjo ID-Reader Single ID-Card Reader






Banjo ID-Reader

Single ID-Card Reader

Banjo ID-Reader is an excellent choice if you require a quick, flexible and compact instrument to read your ID-Cards.

Banjo increases security, standardizes reading and reduces manual intervention. Furthermore, it is fully compatible with Bio-Rad instruments and **IH**-Central. It can also be used as a back-up system.



* Results/interpretations with Banjo software. If authorized, the user can modify this (with audit trail in the database).

Supreme Security

The unique barcode on each ID-Card allows full traceability, including patient identification, test protocols performed, reading and interpretation of each ID-Card, and prevents errors such as the use of incorrect or expired ID-Cards.



Additional module available: IH-Com

Objective and Standardized

Banjo proven software guarantees objective and standardized reading and interpretation independent of user assessment.

Flexible Data Management

Through the integrated software, the results/interpretations can be displayed, printed and sent to the LIS through **IH**-Com.

The database allows you to archive data and group or search it using different criteria, thereby ensuring the integrity of allocated results.



Inserting an ID-Card

Quick and Easy

Simply insert the ID-Card, close the cover and in an instant the results/interpretations are available.

Customize or Extend

Banjo can be used in a stand-alone configuration or connected to any Bio-Rad pipetting system. This enables you to customize your laboratory according to your current and future requirements.


Validation and Control

A high resolution camera guarantees clear images that a user can examine in order to validate or even modify* results/interpretations reported by Banjo.

* Depending on authorization level with audit trail in the database.



ID-Card reading



Results validation

Specifications

Electrical Data		Read
Voltage	115-230 VAC	
Power fluctuation	± 10%	
Transient overvoltage	category II	
Frequency	50/60 Hz	
Power consumption	max. 25 VA	Ma
Environmental Conditions		Re
Operating temperature	15°C to 35°C	Po
	(59°F to 95°F)	• Hi
Operating humidity	30% to 80% rh	• 0
Altitude maximum	2,000 m	= 0
Dimensions		= Ci = Re
Width	250 mm	
Height	150 mm	• C
Depth	390 mm	• C
Weight	5.3 kg	
Capacity		
ID-Card	1	
Emissions		
Heat emission	10 W	
Noise level	max. 53 dB(A)	
Pollution level	2	

Performance

Reading time (1 ID-Card)

Main Features

- Reading and interpretation of ID-Cards
- Positive identification
- High resolution camera
- Only one connection to the LIS through IH-Com
- Compact
- Results/interpretations within seconds
- Complete traceability of tests, results and operator
- CE compliant according to IVD Directive 98/79/EC

- **Ordering Information**
- Catalog # Desi 009945 Ban 009980 PC 009010 IH-C
- Description Banjo ID-Reader PC Unit IH-Com Kit for Reader

Visit www.bio-rad.com/immunohematology for more information.

< 2 sec





Bio-Rad Laboratories

Clinical Diagnostics Group
 Website
 www.bio-rad.com/diagnostics
 Australia
 61-2-9914-2800
 Austral
 33-1-877-8901
 Belgium
 +32 (3)710-53-00
 Brazil
 +55 (31)3689-6600

 Canada
 1-514-334-4372
 China
 86-21-61698500
 Czech
 Republic
 420-241-430-532
 Denmark
 +45-4452-1000
 Finland
 358-9-804-22-00

 France
 33-1-47-95-60-00
 Germany
 +49 (0)89-318-840
 Greece
 30-210-7774396
 Hong Kong
 852-2789-3300
 Hungary
 +36-1-459-6100

 India
 1800-180-1224
 Israel
 972-3-96360500
 Italy
 +39-02-216091
 Japan
 81-3-3661-7070
 Korea
 82-2-3473-4460
 Mexico
 +52 (55)5488-7670

 The Netherlands
 +31-318-540666
 New Zealand
 64-9-415-2280
 Norway
 +47-23-38-41-30
 Poland
 48-22-331999
 Portugal
 351-21-472-7700

 Russia
 +7-495-721-1404
 Singapore
 65-6415-3170
 South Africa
 27-11-442-85-08
 Spain
 34-91-590-5200
 Sweden
 46-8-555-127-00

 Switzerland
 +41 (0)26-674-55-05/06
 Taiwan

